



Hot Dog Roller Grills, Slanted

model #: 8027-SLT, 8027SX-SLT, 8033SX-SLT, 8036-SLT, 8036SX-SLT, 8045W-SLT, 8045SXW-SLT, 8055SX-SLT

When it comes to making money, you can't go wrong with an original. And with the special merchandising feature of slanted rollers, an original has gotten even better. Operators will tell you Nemco—the original hot dog roller grill—has always been famous for its superior diehard cooking performance.

Its time-tested, low-maintenance design will serve you for years and forever satisfy your customers with the tastiest, juiciest hot dogs. 360° roller rotation prevents residue buildup, while individual roller heating elements ensure heating consistency. Gripslt, Nemco's optimized non-slip technology, allows for turning of a variety of items, including breaded and sugary-coated products, all while keeping clean-up easy.

STANDARD FEATURES


- Rugged stainless steel and aluminum construction
- Simplest installation - plugs into any outlet with corresponding voltage
- Rollers available in either standard chrome, or Gripslt which cleans easily with just a damp sponge
- Two individual heat controls for front and rear rollers
- Temperature control with seven heat settings
- Roller grills slant 7° for effective merchandising
- Individual heating element in each roller with superior temperature consistency from end to end
- Sealed motor with ball bearings to prevent grease leakage out of motor
- Rollers rotate at a complete 360° turn by means of a roller sprocket, motor sprocket and chain
- End bearing and grease barrier double protect against grease seepage
- Removable grease drip pan
- Preheat time is 20 minutes
- Full one year factory warranty
- NSF and cETLus certified

ACCESSORIES

- Food Safety Guards available for all roller grills; offers sanitary protection
- Heated and humidified Bun Warmers keep buns fresh and ready to serve
- Bun boxes come in a variety of sizes for great merchandising
- Condiment and dispensing solutions



Hot Dog Roller Grills, Slanted



Model #	Description	Size	Volts	Watts	Amps	No. of Rollers	No. of Cords	No. of 5" Franks Per Hour	Unit Weight	Shipping Weight
8027-SLT 8027SX-SLT	Slanted, 27 Hot Dogs, Chrome Slanted, 27 Hot Dogs, Gripslt	22¼" x 16¼" x 10¼"	120	950	7.9	10	1 / 5-15P	27-540	37 lbs	44 lbs
8033SX-SLT	Slanted, 33 Hot Dogs, Gripslt	23¾" x 20⅞" x 10¾"	120	1200	10.0	12	1 / 5-15P	33-660	29 lbs	35 lbs
8036 8036SX-SLT	Slanted, 36 Hot Dogs, Chrome Slanted, 36 Hot Dogs, Gripslt	29½" x 16¼" x 10¼"	120	1500	12.5	10	1 / 5-15P	36-720	37 lbs	45 lbs
8045W-SLT 8045SXW-SLT	Wide, Slanted, 45 Hot Dogs, Chrome Wide, Slanted, 45 Hot Dogs, Gripslt	35½" x 16¼" x 10¼"	120	1800	15.0	10	1 / 5-15P	45-900	54 lbs	63 lbs
8055SX-SLT	Slanted, 55 Hot Dogs, Gripslt	35¾" x 20⅞" x 10¾"	120	1560	13.0	12	1 / 5-15P	55-1100	62 lbs	72 lbs

*Units compatible with 220 volts and 230 volts also available.

TYPICAL SPECIFICATIONS

Roller Grill shall be stainless steel and heavy-duty aluminum construction and use non-slip *Gripslt* or chrome rollers and tubular heating elements. Rollers slant from front to rear of unit by 7° for effective merchandising. One element shall be contained in each roller. Seven setting infinite temperature control provides flexible cooking and holding. Unit shall have a sealed motor with ball bearings for long life. Each roller shall have a PTFE end bearing and FEP grease barrier combination. The unit shall be equipped with a pilot light, lighted rocker switch and operate on 120V (60Hz) with (1) or (2) 6' cord(s) and NEMA 5-15P, 5-20P, on 220V (60Hz) with a 6' cord and NEMA 6-15P, or on 230V (50Hz) with a 6' cord and SCHUKO CEE7-7. Roller grills shall carry the approval of cETLus (120V, 220V), shall be listed with the National Sanitation Foundation (120V), and shall carry the approval of CE (230V).